

rolesFromAdaptor

```
[cn=developer,ou=groups,dc=example,dc=com, cn=user,ou=groups,dc=example,dc=com,  
cn=admin,ou=groups,dc=example,dc=com, cn=analyst,ou=groups,dc=example,dc=com,  
cn=manager,ou=groups,dc=example,dc=com]
```

userImpl

```
UserImpl [id=fde, roles=[cn=developer,ou=groups,dc=example,dc=com,  
cn=user,ou=groups,dc=example,dc=com, cn=admin,ou=groups,dc=example,dc=com,  
cn=analyst,ou=groups,dc=example,dc=com, cn=manager,ou=groups,dc=example,dc=com],  
groups=[], properties={}]
```

```
[5/6/17 12:15:12:883 BST] 0000010c ServerSession I
```

```
org.apache.sshd.server.session.ServerSession <init> Server session created from  
/127.0.0.1:35562
```

```
[5/6/17 12:15:12:886 BST] 0000010c ServerSession I
```

```
org.apache.sshd.common.session.AbstractSession negotiate Kex: server->client aes128-ctr  
hmac-md5 none
```

```
[5/6/17 12:15:12:888 BST] 0000010c ServerSession I
```

```
org.apache.sshd.common.session.AbstractSession negotiate Kex: client->server aes128-ctr  
hmac-md5 none
```

```
[5/6/17 12:15:20:204 BST] 0000010a ServerUserAut I
```

```
org.apache.sshd.server.session.ServerUserAuthService process Session
```

```
fde@/127.0.0.1:35562 authenticated
```

```
[5/6/17 12:15:20:206 BST] 00000103 ChannelSessio I
```

```
org.apache.sshd.server.channel.ChannelSession handleExec Executing command:  
git-upload-pack '/jbpmp-playground'
```

All threads



Sshd-ssherver threads

